

DECLARATION OF PERFORMANCE

GX-01-0012-04

6. Harmonised standard

EN 13171:2012+A1:2015

Notified body: NB 0672 - MPA Stuttgart

1. Unique identification code of the product type							
GUTEX Thermoflex							
2. Purpose of use							
Thermal insulation for buildings							
3. Manufacturer							
GUTEX Holzfaserplattenwerk H. Henselmann GmbH + Co KG Gutenburg 5 79761 Waldshut-Tiengen Germany							
4. Authorised representative							
No authorised representative							
5. System for the assessment and verification of constancy of performance							
System 3							

7. Declared performance

Essential features	stated as	Performance			
	Thermal resistance R_D per nominal thickness d_N	see table below 1)			
Thermal resistance	Nominal thermal conductivity λ_D [W/mK]	0.036			
	Tolerance class	Т3			
Reaction to fire	Fire reaction Euro Class as per EN 13501-1	E			
Durability of fire behaviour under the influence of heat, weathering, ageing/degradation	Properties of durability	NPD			
	Thermal resistance $R_{\scriptscriptstyle D}$ per nominal thickness $d_{\scriptscriptstyle N}$	NPD			
Durability of the thermal resistance under the	Thermal conductivity $\lambda_D^{}[\text{W/mK}]$	NPD			
influence of heat, weathering, ageing/degradation	Properties of durability	NPD			
	Dimensional stability	NPD			
Compugative etwoesth	Compressive stress	CS(10/Y)100			
Compressive strength	Point load	NPD			
Tancila / flavoural atmospath	Tensile strength perpendicular to the panel plane	TR1			
Tensile / flexural strength	Tensile strength parallel to the panel plane	NPD			
Durability of compressive strength under the influence of ageing/degradation	Creep behaviour under compressive stress	NPD			
Water permeability	Short-term water absorption	NPD			
Water vapour permeability	Water vapour transmission	MU2			
	Dynamic stiffness	NPD			
Impact sound transmission (for floors)	Thickness	NPD			
	Compressibility	NPD			
	Air flow resistivity	AF _r 5			
Sound absorption level	Sound absorption	NPD			
airborne sound insulation index	Air flow resistivity	AF _r 5			
Release of dangerous substances, discharge into the building interior	Release of dangerous substances	NPD			
smoldering behavior	smoldering behavior	NPD			

NPD: No Performance Determined

1) Thermal resistance per panel thickness													
Thickness d _N [mm]	30	40	50	60	80	100	120	140	160	180	200	220	240
$R_D [m^2 K/W]$	0.80	1.10	1.35	1.65	2.20	2.75	3.30	3.85	4.40	5.00	5.55	6.10	6.65

The performance of the above product corresponds to the declared performances.

The manufacturer named above is solely responsible for preparing the declaration of performance in accordance with Regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer



Waldshut-Tiengen, 11/08/2023 \cdot Claudio Thoma, Managing Director

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland

