

Declaration of Performance 0068 – CPR – 022/2014 - DP011EN1442100

1. **Unique identification code of the product-type:** Aquabond
2. **Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):**
 Product name: Aquabond
 Production date and batch are printed on the package.
 Production plant: Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN)
3. **Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:**
 Products and systems for the protection and restoration of concrete structures – Part 2 : Systems to protect concrete surfaces in accordance with UNI EN 1504-2.
 Intended use: superficial protection - coating.
 Product used in buildings and civil engineer works.
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):**
 Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN) – www.diasen.com
5. **Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**
 Not applicable.
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**
 System 2+.
7. **In case of the declaration of performance concerning a construction product covered by a harmonized standard:**
 Istituto di Ricerche e Collaudi M. Masini - Identification number: 0068
 Has done:
 1. initial inspection of the production plant and production control;
 2. supervision, assessment and evaluation of plant production control. According to system 2+ and issued the certificate of conformity of the plant production control n. 0068-CPR-022/2014 of 27/03/2014.

8. Declared performance:

Essential Characteristics	Performance	Harmonized Technical Specification
Vapour permeability value	$S_d = 0,49 \text{ m}$	UNI EN ISO 7783
Capillary absorption and water permeability	NPD	UNI EN 1062-3
Adhesion	NPD	UNI EN 1542
Fire resistance	NPD	UNI EN 13501-1
Dangerous substances	Read the SDS	EC Regulation n. 1272/2008

9. **The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**



Signed for and on behalf of the manufacturer by: Diego Mingarelli – Legal representative

Sassoferrato, 16/07/2014

DiaSen srl
 Z. Ind.le Berbentina, 5
 60041 Sassoferrato (AN)
 P. IVA/C.S. 01553210426



R04_7.2_SGQA rev 0 del 30/06/2013

 0068	 Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy www.diasen.com										
<p style="text-align: center;">14 CPR – 022/2014 UNI EN 1504-2 AQUABOND</p> <p style="text-align: center;"><i>Products and systems for the protection and restoration of concrete structures – Part 2 : Systems to protect concrete surfaces</i></p> <table border="0"> <tr> <td>Vapour permeability value</td> <td>$S_d = 0,49 \text{ m}$</td> </tr> <tr> <td>Capillary absorption and water permeability</td> <td>NPD</td> </tr> <tr> <td>Adhesion</td> <td>NPD</td> </tr> <tr> <td>Fire resi stance</td> <td>NPD</td> </tr> <tr> <td>Dangerous substances</td> <td>Read the SDS</td> </tr> </table>		Vapour permeability value	$S_d = 0,49 \text{ m}$	Capillary absorption and water permeability	NPD	Adhesion	NPD	Fire resi stance	NPD	Dangerous substances	Read the SDS
Vapour permeability value	$S_d = 0,49 \text{ m}$										
Capillary absorption and water permeability	NPD										
Adhesion	NPD										
Fire resi stance	NPD										
Dangerous substances	Read the SDS										