

Declaration of Performance 0068 – CPR – 021/2014 – DP003EN1415300

1. **Unique identification code of the product-type:** Diathonite Screed
2. **Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):**
 Product name: Diathonite Screed
 Production date and batch are printed on the package.
 Production plant: Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN)
3. **Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:**
 Screed and materials for screed – Materials for screed – Properties and requirements.
 In accordance with UNI EN 13813:2004 regulation.
 Product used in buildings and in civil engineer works.
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):**
 Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN) – www.diasen.com
5. **Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**
 Not applicable.
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**
 System 2+.
7. **In case of the declaration of performance concerning a construction product covered by a harmonized standard:**
 Istituto di Ricerche e Collaudi M. Masini – Identification num.: 0068
 Has done:
 1. initial inspection of the production plant and production control;
 2. supervision, assessment and evaluation of plant production control. According to system 2+ and issued the certificate of conformity of the plant production control n. 0068-CPR-021/2014 of 27/03/2014.
8. **Declared performance:**

Essential Characteristics	Performance	Harmonized Technical Specification
Compression resistance	> 5,00 N/mm ² class C5	UNI EN 13813
Bending resistance	> 1,00 N/mm ² class F1	UNI EN 13813
Fire reaction	Class A1	UNI EN 13501-1
Thermal conductivity	λ= 0,060 W/mK	UNI EN 12667
Dangerous substances	Read the SDS	EC Regulation n. 1272/2008



9. **The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by: Diego Mingarelli – Legal represe

Sassoferrato, 31/03/2014

R04_7.2_SGQA rev 0 of 30/06/2013


DiaSen srl
 Z. Ind.le Berbentina, 5
 60041 Sassoferrato (AN)
 P. IVA/C.S. 01553210426

	 <p>Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy www.diasen.com</p>										
<p>14 CPR – 021/2014 UNI EN 13813 DIATHONITE SCREED <i>Specifications for mortar for masonry – Part 1: Mortar for internal and external plaster.</i></p> <table border="0"> <tr> <td>Compression resistance</td> <td>> 5,00 N/mm² class C5</td> </tr> <tr> <td>Bending resistance</td> <td>> 1,00 N/mm² class F1</td> </tr> <tr> <td>Fire reaction</td> <td>Class A1</td> </tr> <tr> <td>Thermal conductivity</td> <td>λ= 0,060 W/mK</td> </tr> <tr> <td>Dangerous substances</td> <td>Read the SDS</td> </tr> </table>		Compression resistance	> 5,00 N/mm ² class C5	Bending resistance	> 1,00 N/mm ² class F1	Fire reaction	Class A1	Thermal conductivity	λ= 0,060 W/mK	Dangerous substances	Read the SDS
Compression resistance	> 5,00 N/mm ² class C5										
Bending resistance	> 1,00 N/mm ² class F1										
Fire reaction	Class A1										
Thermal conductivity	λ= 0,060 W/mK										
Dangerous substances	Read the SDS										