

Declaration of Performance 0068 - CPR - 021/2014 - DP003EN1415300

- 1. Unique identification code of the product-type: Diathonite Screed
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Product name: Diathonite Screed

Production date and batch are printed on the package.

Production plant: Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN)

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Screed and materials for screed – Materials for screed – Properties and requirements.

In accordance with UNI EN 13813:2004 regulation.

Product used in buildings and in civil engineer works.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN) - www.diasen.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+.

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Istituto di Ricerche e Collaudi M. Masini – Identification num.: 0068

Has done

- 1. initial inspection of the production plant and production control;
- 2. supervision, assessment and evaluation of plant production control. According to system 2+ and issued the certificate of conformity of the plant production control n. 0068-CPR-021/2014 of 27/03/2014.
- 8. Declared performance:

Essential Characteristics	Performance	Harmonized Technical Specification
Compression resistance	> 5,00 N/mm² class C5	UNI EN 13813
Bending resistance	> 1,00 N/mm² class F1	UNI EN 13813
Fire reaction	Class A1	UNI EN 13501-1
Thermal conductivity	λ= 0,060 W/mK	UNI EN 12667
Dangerous substances	Read the SDS	EC Regulation n. 1272/2008

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Diego Mingarelli – Legal represe

Sassoferrato, 31/03/2014

R04_7.2_SGQA rev 0 of 30/06/2013













Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy ww.diasen.com

14 CPR - 021/2014 UNI EN 13813 DIATHONITE SCREED

Specifications for mortar for masonry – Part 1: Mortar for internal and external

plaster.

Compression resistance > 5,00 N/mm² class C5

Bending resistance > 1,00 N/mm² class F1

Fire reaction Class A1

Thermal conductivity λ = 0,060 W/mK

Dangerous substances Read the SDS





For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland

