# AURO

524( Vers		lantodecor premium wall paint evision date 13-Feb-2024	Print date 22-Apr-2024	
SE	CTION 1: Identification of the	substance/mixture and of the company/undertaking		
1.1	Product identifier			
	Trade name/designation			
	5240000	Plantodecor premium wall paint		
1.2	Relevant identified uses of the s	substance or mixture and uses advised against		
	Relevant identified uses	, and the second s		
	Innenanstriche für Wände und De	cken (matt)		
1.3	Details of the supplier of the sat			
	Supplier			
	AURO Pflanzenchemie AG			
	Alte Frankfurter Straße 211 A	Telephone: +49 531 28141-0		
	38122 Braunschweig	Telefax: +49 531 28141-72 E-mail: info@auro.de		
	Germany	Website: www.auro.de		
	Importer/Only Representative			
	AURO Pflanzenchemie AG			
	Alte Frankfurter Straße 211 A	Telephone: +49 531 28141-0		
	38122 Braunschweig Germany	Telefax: +49 531 28141-72 E-mail: info@auro.de		
		Website: www.auro.de		
	Department responsible for info	ormation		
	E-mail (competent person)	msds@auro.de		
1.4				
	Emergency telephone number: +49 531 28141-34 Only available during office hours.			
SE	CTION 2: Hazards identificati	on		
2.1 Classification of the substance or mixture				
	Classification according to Reg	ulation (EC) No 1272/2008 [CLP]		
	The mixture is classified as not ha	zardous according to regulation (EC) No 1272/2008 [CLP].		
2.2	Label elements			
	Labelling according to Regulation (EC) No. 1272/2008 [CLP]			
Hazard pictograms				
	not applicable			
	Signal word			
	not applicable			
	Hazard statements			
	not applicable			
	Precautionary statements			
	not applicable			
	Hazard components for labelling			
	not applicable			
	Supplemental hazard informatic EUH211 Warn		not broothe enrouser wist	
2.3	Other hazards	ing! Hazardous respirable droplets may be formed when sprayed. Do	not breathe spray of mist.	
2.3		not meet the PBT/vPvB criteria according to REACH, annex XIII.		
SE	CTION 3: Composition/inform			
3.2	Mixtures			
	Description			
	Hazardous ingredients			
	nazaravas nigreatents			



240000 ersion 4.1		Plantodecor premium wall paint Revision date 13-Feb-2024 Pl	
	CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
	3811-73-2 223-296-5 -	Pyridine-2-thiol 1-oxide, sodium salt       01-2119493385-28       Acute Tox. 4 H302 / Acute Tox. 4 H312 / Skin Irrit. 2 H315 / Eye Irrit. 2A H319 / Acute Tox. 4       H332 / Aquatic Acute 1 H400 (M = 100,00) / Aquatic Chronic 1 H410 (M = 10,00)       ATE (oral): = 1,208 mg/kg bw       ATE (inhalative): = 1.08 mg/m³ (4 h)       ATE (dermal): = 2,000 mg/kg bw	< 0,025

Full text of H- and EUH-statements: see section 16.Full text of H-phrases: see section 16.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### **Following inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### **Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### Self-protection of the first aider

First aider: Pay attention to self-protection!

#### Most important symptoms and effects, both acute and delayed 4.2

#### Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

#### Unsuitable extinguishing media

Strong water jet

#### 5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### 5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

#### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.



5240000	Plantodecor premium wall paint
Version 4.1	Revision date 13-Feb-2024

#### 6.3 Methods and material for containment and cleaning up

#### For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

### For cleaning up

Clean using cleansing agents. Do not use solvents.

#### 6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: refer to section 8 Disposal: see section 13

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

#### Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. Personal protection equipment: see section 8 Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Storage class LGK12 - non-combustible liquids that cannot be assigned to any of the above storage classes

#### Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3 Specific end use(s)

Observe technical data sheet.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational exposure limit values

No data available

**Biological limit values** 

No data available

#### 8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

#### Personal protection equipment

#### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

#### Hand protection

Suitable material: NBR (Nitrile rubber) Thickness of the glove material >= 0.4 mm Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles:EN ISO 374

#### Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.



		r premium wall paint te 13-Feb-2024	Print date 22-Apr-2024
	Eye/face protection	· · · ·	•
*	Eye glasses with side protection: EN 166		
	Body protection		
	When handling with chemical substances, p	rotective clothing with CE-labels including the four cor	ntrol digits must be worn.
	Environmental exposure controls		
-	Do not allow to enter into surface water or d	ains.	
SE	CTION 9: Physical and chemical prop	erties	
9.1	Information on basic physical and chemic	cal properties	
	Physical state	Liquid	
	Colour	refer to label	
	Odour	characteristic	
	рН	not determined	
	Melting point/freezing point	not determined	
	Initial boiling point and boiling range	not determined	
	Flash point	not determined	
	flammability	not applicable	
	Lower explosion limit at 20°C	not determined	
	Upper explosion limit at 20°C	not determined	
	Vapour pressure at 20°C	23.531 mbar	
	Relative vapour density	not applicable	
	Density at 20 °C	1.6 kg/l	
	Water solubility at 20°C	practically insoluble	
	Partition coefficient: n-octanol/water	see section 12	
	Ignition temperature in °C	not determined	
	Decomposition temperature	not determined	
	Viscosity at 40 °C:	not determined	
9.2	Other information		

not applicable

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

#### 10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

#### 10.5 Incompatible materials

No further relevant information available.

#### **10.6 Hazardous decomposition products**

\* Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute toxicity

Based on available data, the classification criteria are not met.



5240000	Plantod
Version 4.1	Revisio

Plantodecor premium wall paint Revision date 13-Feb-2024

- \* **Pyridine-2-thiol 1-oxide, sodium salt** LD50: oral (Rat): = 1,208 mg/kg bw
- \* LC50: inhalative (Rat): = 1.08 mg/m<sup>3</sup> (4 h)
- \* LD50: dermal (Rat): = 2,000 mg/kg bw

## Skin corrosion/irritation

Based on available data, the classification criteria are not met.

## Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

## Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### 11.2 Information on other hazards

#### \* Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Based on available data, the classification criteria are not met.

- Acute (short-term) fish toxicity
- Pyridine-2-thiol 1-oxide, sodium salt LC50: (Oncorhynchus mykiss (Rainbow trout)): = 0.007 mg/L (96 h) Method: OECD 203

### Acute (short-term) toxicity to algae and cyanobacteria

- \* NOEC (Selenastrum capricornutum): = 0.08 mg/L (72 h) Method: OECD 201
- \* EC50 (Selenastrum capricornutum): = 0.46 mg/L (72 h) Method: OECD 201
- Acute (short-term) toxicity to crustacea \* EC50 (Daphnia magna (Big water flea)): = 0.022 mg/L (48 h) Method: OECD 202

### 12.2 Persistence and degradability

No information available.

### 12.3 Bioaccumulative potential

\* Partition coefficient: n-octanol/water = 0 (Pyridine-2-thiol 1-oxide, sodium salt)

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6\* Endocrine disrupting properties



5240000 Version 4.1 Plantodecor premium wall paint Revision date 13-Feb-2024

Print date 22-Apr-2024

No information available.

## 12.7 Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/ EC, covering waste and dangerous waste.

#### Waste codes/waste designations according to EWC/AVV

080120 - aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

#### Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

#### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

not applicable

#### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

No dangerous good in sense of these transport regulations.

#### Sea transport (IMDG)

No dangerous good in sense of these transport regulations.

#### Air transport (ICAO-TI / IATA-DGR)

No dangerous good in sense of these transport regulations.

#### 14.3 Transport hazard class(es)

not applicable

### 14.4 Packing group

not applicable

## 14.5 Environmental hazards

Land transport (ADR/RID) Sea transport (IMDG) not applicable not applicable

#### 14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

## 14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

## 14.8 Additional information

Land transport (ADR/RID)

not applicable

## Sea transport (IMDG)

not applicable

## Air transport (ICAO-TI / IATA-DGR)

not applicable

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

## EU legislation

## **Restrictions of occupation**

\* Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.
\* Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

## Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 0 g/l



5240000	Plantodecor premium wall paint	
Version 4.1	Revision date 13-Feb-2024	Pr

Print date 22-Apr-2024

### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

\* VOC limit value: 2004/42/IIA(a): 30 g/l (2010)

This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] Hazard categories / Named dangerous substances

This product is not classified according to Directive 2012/18/EU.

## National regulations

\* Observe in addition any national regulations!

#### 15.2 Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

	REACH No.	Substance name	CAS No. EC No.
*	01-2119493385-28	Pyridine-2-thiol 1-oxide, sodium salt	3811-73-2 223-296-5

## **SECTION 16: Other information**

### List of relevant hazard statements and/or precautionary statements from sections 2 to 15

	H302	Harmful if swallowed.
*	H312	Harmful in contact with skin.
*	H315	Causes skin irritation.
	H319	Causes serious eye irritation.
	H332	Harmful if inhaled.
	H400	Very toxic to aquatic life.
*	11110	Vany taxia ta aquatia lifa with lang

H410 Very toxic to aquatic life with long lasting effects.

# Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

not applicable

### Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration

EC: European Community

EN: European Standard

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

MWC: Maximum wokplace concentration

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic

PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

## Indication of changes

\* Data changed compared with the previous version.

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



# Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



# Email us

info@ecologicalbuildingsystems.com



# Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland



Discover our solutions online at ecologicalbuildingsystems.com