# AURO

Print date 07-Mar-2024

VHIV	0000 sion 6.0	Special primer Revision date 10-Feb-2024 Print date 07-Mar
		of the substance/mixture and of the company/undertaking
1.1	Product identifier	
	Trade name/designation	
	1170000	Special primer
1.2	UFI: Bolovant identified uses	7441-602D-9008-DMV6 of the substance or mixture and uses advised against
1.2	Relevant identified uses	-
	Plating agent	
1.3	Details of the supplier of	f the safety data sheet
1.0	Supplier	
	AURO Pflanzenchemie A Alte Frankfurter Straße 21 38122 Braunschweig Germany	
	Department responsible	for information
	E-mail (competent person	) msds@auro.de
1.4	Emergency telephone nur Emergency telephone nur Only available during offic	nber: +44 1544388535
SE	CTION 2: Hazards iden	tification
2.1	Classification of the sub	estance or mixture
	Classification according	to Regulation (EC) No 1272/2008 [CLP]
	Flam. Liq. 3; flammable lic Skin Sens. 1; Skin sensitis	us hazardous according to regulation (EC) No 1272/2008 [CLP]. quids; H226 Flammable liquid and vapour. sation; H317 May cause an allergic skin reaction. us to the aquatic environment; H400 Very toxic to aquatic life.
2.2		dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects.
2.2	Aquatic Chronic 1; Hazaro Label elements	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects.
2.2	Aquatic Chronic 1; Hazaro Label elements	
<b>2.2</b>	Aquatic Chronic 1; Hazard Label elements Labelling according to R Hazard pictograms	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects.
<b>2.2</b>	Aquatic Chronic 1; Hazard Label elements Labelling according to F Hazard pictograms GHS02 GHS07 GH	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. Regulation (EC) No. 1272/2008 [CLP]
2.2	Aquatic Chronic 1; Hazard Label elements Labelling according to F Hazard pictograms	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. Regulation (EC) No. 1272/2008 [CLP]
*	Aquatic Chronic 1; Hazard Label elements Labelling according to R Hazard pictograms GHS02 GHS07 GH Signal word	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. Regulation (EC) No. 1272/2008 [CLP]
*	Aquatic Chronic 1; Hazard Label elements Labelling according to F Hazard pictograms GHS02 GHS07 GH Signal word Warning Hazard statements H226	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. Regulation (EC) No. 1272/2008 [CLP]
*	Aquatic Chronic 1; Hazard Label elements Labelling according to F Hazard pictograms GHS02 GHS07 GH Signal word Warning Hazard statements H226 H317	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. <b>Regulation (EC) No. 1272/2008 [CLP]</b>
*	Aquatic Chronic 1; Hazard Label elements Labelling according to F Hazard pictograms GHS02 GHS07 GH Signal word Warning Hazard statements H226 H317 H410	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. Regulation (EC) No. 1272/2008 [CLP]
*	Aquatic Chronic 1; Hazard Label elements Labelling according to R Hazard pictograms GHS02 GHS07 GH Signal word Warning Hazard statements H226 H317 H410 Precautionary statement	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. Regulation (EC) No. 1272/2008 [CLP]
*	Aquatic Chronic 1; Hazard Label elements Labelling according to F Hazard pictograms GHS02 GHS07 GH Signal word Warning Hazard statements H226 H317 H410	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. Regulation (EC) No. 1272/2008 [CLP]
*	Aquatic Chronic 1; Hazard Label elements Labelling according to R Hazard pictograms GHS02 GHS07 GH Signal word Warning Hazard statements H226 H317 H410 Precautionary statement P101 P102 P210	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. Regulation (EC) No. 1272/2008 [CLP]
*	Aquatic Chronic 1; Hazard Label elements Labelling according to R Hazard pictograms GHS02 GHS07 GH Signal word Warning Hazard statements H226 H317 H410 Precautionary statement P101 P102 P210 P273	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects.          Regulation (EC) No. 1272/2008 [CLP]         Image: second secon
*	Aquatic Chronic 1; Hazard Label elements Labelling according to F Hazard pictograms GHS02 GHS07 GH Signal word Warning Hazard statements H226 H317 H410 Precautionary statement P101 P102 P210 P273 P280	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects.          Regulation (EC) No. 1272/2008 [CLP]         Image: style="text-align: center;">Image: style="text-align: center;">Image: style="text-align: center;">Image: style="text-align: style="text-align: center;">Image: style="text-align: style="text-align: center;">Image: style="text-align: style="text-align: style="text-align: center;">Image: style="text-align: style="text-align: style="text-align: center;">Image: style="text-align: style="text-align: style="text-align: style="text-align: center;">Image: style="text-align: s
*	Aquatic Chronic 1; Hazard Label elements Labelling according to R Hazard pictograms GHS02 GHS07 GH Signal word Warning Hazard statements H226 H317 H410 Precautionary statement P101 P102 P210 P273	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. Regulation (EC) No. 1272/2008 [CLP] Flammable liquid and vapour. May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects. Is If medical advice is needed, have product container or label at hand. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Wear protective gloves and eye/face protection. In case of fire: Use extinguishing powder or sand to extinguish.
2.2	Aquatic Chronic 1; Hazard Label elements Labelling according to F Hazard pictograms GHS02 GHS07 GH Signal word Warning Hazard statements H226 H317 H410 Precautionary statement P101 P102 P210 P273 P280 P370 + P378	dous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects.          Regulation (EC) No. 1272/2008 [CLP]         Image: style="text-align: center;">Image: style="text-align: center;">Image: style="text-align: center;">Image: style="text-align: style="text-align: center;">Image: style="text-align: style="text-align: center;">Image: style="text-align: style="text-align: style="text-align: center;">Image: style="text-align: style="text-align: style="text-align: center;">Image: style="text-align: style="text-align: style="text-align: style="text-align: center;">Image: style="text-align: s



1170000 Sp Version 6.0 Re

Special primer Revision date 10-Feb-2024

#### turpentine, oil

Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4-(1-methylethylidene)-cyclohexene and 1-methyl-4-(propan-2-yl)cyclohexa-1,3-diene

#### Supplemental hazard information

not applicable

#### 2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### **SECTION 3: Composition/information on ingredients.**

#### 3.2 Mixtures

#### Description

#### **Hazardous ingredients**

	CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
*	- 939-409-2 -	Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4-(1- methylethylidene)-cyclohexene and 1-methyl-4-(propan-2-yl)cyclohexa-1,3-diene 01-2119969963-17-xxxx Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / Skin Sens. 1B H317 / Aquatic Acute 1 H400 (M = 1,00 ) / Aquatic Chronic 1 H410 (M = 1,00 )	50,0 < 70,0
*	8006-64-2 932-349-8 650-002-00-6	turpentine, oil 01-2119553060-53-0007 Flam. Liq. 3 H226 / Acute Tox. 4 H302 / Asp. Tox. 1 H304 / Acute Tox. 4 H312 / Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Irrit. 2 H319 / Acute Tox. 4 H332 / Aquatic Chronic 2 H411 ATE (oral): = 3,956 mg/kg ATE (oral): = 3,956 mg/kg	5,00 < 7,00

#### Remark

Full text of H- and EUH-statements: see section 16.Full text of H-phrases: see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### **Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### Self-protection of the first aider

First aider: Pay attention to self-protection!

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media



1170000	Special primer
Version 6.0	Revision date 10-Feb-2024

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

#### Unsuitable extinguishing media

Strong water jet

#### 5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### 5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

#### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

#### 6.3 Methods and material for containment and cleaning up

#### For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

#### For cleaning up

Clean using cleansing agents. Do not use solvents.

#### 6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: refer to section 8 Disposal: see section 13

#### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

#### Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. Personal protection equipment: see section 8 Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Advices on general occupational hygiene

When using do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Storage class LGK3 - Flammable liquids

#### Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3 Specific end use(s)

Observe technical data sheet.

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### Occupational exposure limit values

CAS No. Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
------------------------	--------	----------------------------------------------



		ial primer sion date 10-Feb-2024		Print date 07-Mar-202
	8006-64-2 turpentine, oil		WEL	566 / 850 ( - ) mg/m <sup>3</sup>
	Additional information			
	Long-term: Long-term occupational ex short-term: short-term occupational ex			
	Biological limit values			
	No data available			
8.2	Exposure controls			
	Provide good ventilation. This can be a	achieved with local or room s	uction.	
	Personal protection equipment			
	Respiratory protection			
	In case of inadequate ventilation weat	r respiratory protection.		
	Hand protection			
	Suitable material: NBR (Nitrile rubber) Thickness of the glove material >= 0.4 Breakthrough time >= 480 min			
	with the supplier of these gloves. Obs	erve the instructions and det netration time of glove mater	ails for use, storage	protective gloves mentioned above together , maintenance and replacement provided by tensity and duration of exposure to skin.
	Skin protection			
	Barrier creams can help protecting ex	posed skin areas. In no case	should they be use	ed after contact.
	Eye/face protection			
*	Eye glasses with side protection: EN	166		
	Body protection		0 F I I I I I I I	
	When handling with chemical substar	ices, protective clothing with	CE-labels including	the four control digits must be worn.
Environmental exposure controls Do not allow to enter into surface water or drains.				
95	CTION 9: Physical and chemical			
	-			
9.1	Information on basic physical and			
	Physical state	Liquid		
	Colour	refer to label		
	Odour	characteristic		
	рН	not determine		
	Melting point/freezing point	not determine	ed	
	Initial boiling point and boiling range	not determine	d	
	Flash point	53 °C		
	flammability	Flammable lic	quid and vapour.	
	Lower explosion limit at 20°C	not determine	d	
	Upper explosion limit at 20°C	not determine	d	
	Vapour pressure at 20°C	2.661 mbar		
	Relative vapour density	not applicable	)	
	Density at 20 °C	0.9 kg/l		
	Water solubility at 20°C	practically ins	oluble	
	Partition coefficient: n-octanol/water	see section 1		
	Ignition temperature in °C	not determine		
	Decomposition temperature	not determine		
	Viscosity at 20 °C:	< 220 mm²/s	iu i	
• •		< 220 mm²/S		
9.2	Other information			
	not applicable			



1170000Special primerVersion 6.0Revision date 10-Feb-2024

Print date 07-Mar-2024

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

#### **10.3 Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

#### 10.5 Incompatible materials

No further relevant information available.

#### 10.6 Hazardous decomposition products

\* Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### turpentine, oil

LD50: oral (Rat): = 3,956 mg/kg

\* LD50: oral (Rat): = 3,956 mg/kg

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

May cause an allergic skin reaction.

#### Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

# STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### **11.2** Information on other hazards

#### \* Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

#### Acute (short-term) fish toxicity

# AURO

	000 ion 6.0	Special primer Revision date 10-Feb-2024	Print date 07-Mar-2024	
÷	Reaction mass of 1-Met methyl-4-(propan-2-yl)cy LC50: (Danio rerio (zebra		-cyclohexene and 1-	
*		<b>ty to algae and cyanobacteria</b> bspicatus): 0.42 mg/L (72 h)		
*	Acute (short-term) toxic EC50 (Daphnia magna (E	<b>ty to crustacea</b> g water flea)): 0.48 mg/L (48 h)		
12.2	Persistence and degrad	bility		
	No information available.			
12.3	Bioaccumulative potent	al		
*		nol/water = 4.88 (Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexer xene and 1-methyl-4-(propan-2-yl)cyclohexa-1,3-diene)	ne and 1-Methyl-4-(1-	
12.4	Mobility in soil			
	No information available.			
12.5	Results of PBT and vPv	assessment		
	The substances in the mi	ture do not meet the PBT/vPvB criteria according to REACH, annex XIII.		
12.6	* Endocrine disrupting pr	perties		
	No information available.			
12.7	Other adverse effects			
	No information available.			
SE	CTION 13: Disposal co	nsiderations		
13.1	Waste treatment metho	S		
	Product/Packaging disp	sal		
	Do not empty into drains; EC, covering waste and c	lispose of this material and its container in a safe way. Waste disposal acco angerous waste.	ording to directive 2008/98/	
	Waste codes/waste des	gnations according to EWC/AVV		
	080111* - Waste paint and varnish containing organic solvents or other dangerous substances			
	Other disposal recomm	ndations		
	Non-contaminated packa	es may be recycled. Vessels not properly emptied are special waste.		
SE	CTION 14: Transport i	formation		
14.1	UN number or ID number			
	UN 1263			
14.2	UN proper shipping nam	e		
	Land transport (ADR/RI	)		
	Paint			
	Sea transport (IMDG)			
	Paint			
	<b>Air transport (ICAO-TI /</b> Paint	ATA-DGR)		
14.3	Transport hazard class	s)		
	Land transport (ADR/RID	3		
	Sea transport (IMDG)	3		
111	Air transport (ICAO-TI / IA Packing group	ΓA-DGR) 3		
14.4	Land transport (ADR/RID	111		
	Sea transport (IMDG)			
	Air transport (ICAO-TI / IA			
14.5	Environmental hazards			
	Land transport (ADR/RID	ENVIRONMENTALLY HAZARDOUS		
	Sea transport (IMDG)	Marine pollutant		
14.6	Special precautions for	iser		

\* Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case



Version 6.0 of an accident or leakage.

1170000

Special primer Revision date 10-Feb-2024

of an accident or leakage. Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

#### 14.8 Additional information

#### Land transport (ADR/RID)

Tunnel restriction code: D/E

Limited quantity (LQ): 5 ltr Hazard identification number (Kemler No.): 30

#### Sea transport (IMDG)

EmS-No.: F-E, S-E Limited quantity (LQ): 5 Itr

> Air transport (ICAO-TI / IATA-DGR) not applicable

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

#### **Restrictions of occupation**

\* Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

#### Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

\* VOC value: 609 g/l

#### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

- \* VOC limit value: 2004/42/IIA(h): 750 g/l (2010)
- Maximum VOC content of the product in a ready to use condition: 609

This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.

# Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] Hazard categories / Named dangerous substances

E1 Hazardous to the aquatic environment in Category Acute 1 or Chronic 1

- Quantity 1: 100t; Quantity 2: 200t P5c FLAMMABLE LIQUIDS
- Quantity 1: 5,000t; Quantity 2: 50,000t

#### National regulations

Observe in addition any national regulations!

#### 15.2 Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

	REACH No.	Substance name	CAS No. EC No.
*	01-2119969963-17-xxxx	Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4- (1-methylethylidene)-cyclohexene and 1-methyl-4-(propan-2- yl)cyclohexa-1,3-diene	- 939-409-2
*	01-2119553060-53-0007		8006-64-2 932-349-8

#### **SECTION 16: Other information**

#### List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.



1170000	Special primer				
Version 6.0	Revision date 10-Feb-2024	Print date 07-Mar-2024			
H410 H411	Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects.				
	for mixtures and used evaluation method according to regulati	on (EC) No 1272/2008 [CL B]			
	•••	OII (EC) NO 1272/2008 [CLP]			
Flam. Liq. 3	On basis of test data.				
Skin Sens. 1	Calculation method.				
Aquatic Acute 1					
Aquatic Chronic					
Abbreviations a	and acronyms				
	Agreement concerning the International Carriage of Dangerous Ge	oods by Road			
	nal Exposure Limit Value				
BLV: Biological					
	Abstracts Service				
CLP: Classificat	CLP: Classification, Labelling and Packaging				
	CMR: Carcinogenic, Mutagenic and Reprotoxic				
	DIN: German Institute for Standardization / German industrial standard				
	DNEL: Derived No-Effect Level				
	EAKV: European Waste Catalogue Directive				
	EC: Effective Concentration				
	EC: European Community EN: European Standard				
	IATA-DGR: International Air Transport Association – Dangerous Goods Regulations				
	IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk				
	CAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air				
	ernational Maritime Code for Dangerous Goods				
	al Organization for Standardization				
LC: Lethal Cond					
LD: Lethal Dose					
MWC: Maximum	n wokplace concentration				
MARPOL: Mariti	ime Pollution: The International Convention for the Prevention of Po	ollution from Ships			
	ation for Economic Cooperation and Development				
	PBT: persistent, bioaccumulative, toxic				
	PNEC: Predicted No Effect Concentration				
	RID: Regulations concerning the International Carriage of Dangerous Goods by Rail				
••••••••	UN: United Nations				
	VOC: Volatile Organic Compounds vPvB: very persistent and very bioaccumulative				
	-				
Indication of changes					

\* Data changed compared with the previous version.

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



# Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



# Email us

info@ecologicalbuildingsystems.com



# Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland



Discover our solutions online at ecologicalbuildingsystems.com