AURO

vers	0090 sion 9.0	Hard oil, white Revision date 01-Aug-2024 Print date 01-Aug-2	
SE	CTION 1: Identification of t	he substance/mixture and of the company/undertaking	
1.1	Product identifier		
	Trade name/designation		
	1260090	Hard oil, white	
	UFI:	8E51-S0EA-V00P-9RM5	
1.2	Relevant identified uses of th	e substance or mixture and uses advised against	
	Relevant identified uses	-	
	Plating agent		
1.3	Details of the supplier of the	safety data sheet	
	Supplier		
	AURO Pflanzenchemie AG		
	Alte Frankfurter Straße 211 A	Telephone: +49 531 28141-0	
	38122 Braunschweig	Telefax: +49 531 28141-72	
	Germany	E-mail: info@auro.de Website: www.auro.de	
	Department responsible for i		
	E-mail (competent person)	msds@auro.de	
1.4			
	Emergency telephone number:		
	Only available during office hou		
SE	CTION 2: Hazards identific	ation	
2.1	Classification of the substan	ce or mixture	
2.1			
	The mixture is classified as haz Flam. Liq. 3; flammable liquids	regulation (EC) No 1272/2008 [CLP] zardous according to regulation (EC) No 1272/2008 [CLP]. ; H226 Flammable liquid and vapour.	
	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous	zardous according to regulation (EC) No 1272/2008 [CLP].	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous Label elements	zardous according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects.	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous Label elements Labelling according to Regul	zardous according to regulation (EC) No 1272/2008 [CLP]. ; H226 Flammable liquid and vapour. n; H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life.	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous Label elements	zardous according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects.	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous 1 Label elements Labelling according to Regul Hazard pictograms	 ardous according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. h; H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. 	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09	 ardous according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. h; H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. 	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09 Signal word	 ardous according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. h; H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. 	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09	 ardous according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. h; H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. 	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09 Signal word Warning Hazard statements	zardous according to regulation (EC) No 1272/2008 [CLP]. ; H226 Flammable liquid and vapour. h; H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. ation (EC) No. 1272/2008 [CLP]	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09 Signal word Warning Hazard statements H226 Fla	 ardous according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. h; H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. 	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09 Signal word Warning Hazard statements H226 Fla H317 Ma	arandous according to regulation (EC) No 1272/2008 [CLP]. ; H226 Flammable liquid and vapour. h; H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. ation (EC) No. 1272/2008 [CLP]	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09 Signal word Warning Hazard statements H226 Fla H317 Ma H410 Ve	 ardous according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. h; H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. 	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09 Signal word Warning Hazard statements H226 Fla H317 Ma H410 Ve Precautionary statements P101 If r	 arardous according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. h; H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. ation (EC) No. 1272/2008 [CLP]	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09 Signal word Warning Hazard statements H226 Fla H317 Ma H410 Ve Precautionary statements P101 If r P102 Ke	Arardous according to regulation (EC) No 1272/2008 [CLP]. (H226 Flammable liquid and vapour. (H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. ation (EC) No. 1272/2008 [CLP] (Market Content of the second seco	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09 Signal word Warning Hazard statements H226 Fla H317 Ma H410 Ve Precautionary statements P101 If r P102 Ke P210 Ke	 Arardous according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. ation (EC) No. 1272/2008 [CLP] <	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09 Signal word Warning Hazard statements H226 Fla H317 Ma H410 Ve Precautionary statements P101 If r P102 Ke P210 Ke P273 Av	 acrodus according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. ation (EC) No. 1272/2008 [CLP] <p< td=""></p<>	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09 Signal word Warning Hazard statements H226 Fla H317 Ma H410 Ve Precautionary statements P101 If r P102 Ke P210 Ke P273 Av P280 Wd	<pre>transmitter in the image of the image.</pre>	
2.2	The mixture is classified as haz Flam. Liq. 3; flammable liquids Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to Aquatic Chronic 1; Hazardous to Label elements Labelling according to Regul Hazard pictograms GHS02 GHS07 GHS09 Signal word Warning Hazard statements H226 Fla H317 Ma H410 Ve Precautionary statements P101 If r P102 Ke P210 Ke P273 Av P280 Wd P370 + P378 In	<pre>tradous according to regulation (EC) No 1272/2008 [CLP]. H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. the aquatic environment; H400 Very toxic to aquatic life. to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects. ation (EC) No. 1272/2008 [CLP] mmable liquid and vapour. y cause an allergic skin reaction. ry toxic to aquatic life with long lasting effects. nedical advice is needed, have product container or label at hand. ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. oid release to the environment. ar protective gloves and eye/face protection. case of fire: Use extinguishing powder or sand to extinguish. </pre>	
2.2	The mixture is classified as hazFlam. Liq. 3; flammable liquidsSkin Sens. 1; Skin sensitisationAquatic Acute 1; Hazardous toAquatic Chronic 1; Hazardous toAquatic Chronic 1; Hazardous toLabel elementsLabel elementsLabelling according to RegulHazard pictograms \bigcirc <t< td=""><td><pre>transmitter in the image of the image.</pre></td></t<>	<pre>transmitter in the image of the image.</pre>	



1260090Hard oil, whiteVersion 9.0Revision date 01-Aug-2024Print date 01-Aug-2024

turpentine, oil

Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4-(1-methylethylidene)-cyclohexene and 1-methyl-4-(propan-2-yl)cyclohexa-1,3-diene

Supplemental hazard information

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EUH211 2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
- 939-409-2 -	Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4-(1- methylethylidene)-cyclohexene and 1-methyl-4-(propan-2-yl)cyclohexa-1,3-diene 01-2119969963-17-xxxx Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / Skin Sens. 1B H317 / Aquatic Acute 1 H400 (M = 1,00) / Aquatic Chronic 1 H410 (M = 1,00)	35,0 < 50,0
8006-64-2 932-349-8 650-002-00-6	turpentine, oil 01-2119553060-53-0007 Flam. Liq. 3 H226 / Acute Tox. 4 H302 / Asp. Tox. 1 H304 / Acute Tox. 4 H312 / Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Irrit. 2 H319 / Acute Tox. 4 H332 / Aquatic Chronic 2 H411 ATE (oral): = 3,956 mg/kg ATE (oral): = 3,956 mg/kg	3,00 < 5,00

Remark

Full text of H- and EUH-statements: see section 16.Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media



1260090	Hard oil, white
Version 9.0	Revision date 01-Aug-2024
· ·	

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: refer to section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. Personal protection equipment: see section 8 Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Storage class LGK3 - Flammable liquids

Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No data available
 Biological limit values

Page 3/8



Print date 01-Aug-2024

1260090 Version 9.0 Hard oil, white Revision date 01-Aug-2024

No data available

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber) Thickness of the glove material >= 0.4 mm Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles:EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166

Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· · · · · · · · · · · · · · · ·	
Physical state	Liquid
Colour	refer to label
Odour	characteristic
рН	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	53 °C
flammability	Flammable liquid and vapour.
Lower explosion limit at 20°C	not determined
Upper explosion limit at 20°C	not determined
Vapour pressure at 20°C	2.497 mbar
Relative vapour density	not applicable
Density at 20 °C	1.0 kg/l
Water solubility at 20°C	practically insoluble
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	not determined
Decomposition temperature	not determined
Viscosity at 20 °C:	< 80 mm²/s
Other information	

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability



1260090	Hard oil, white
Version 9.0	Revision date 01-Aug-2024

Print date 01-Aug-2024

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

turpentine, oil

LD50: oral (Rat): = 3,956 mg/kg

LD50: oral (Rat): = 3,956 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

11.2 Information on other hazards

Endocrine disrupting properties

* This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Acute (short-term) fish toxicity Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4-(1-methylethylidene)-cyclohexene and 1methyl-4-(propan-2-yl)cyclohexa-1,3-diene LC50: (Danio rerio (zebrafish)): 1.3 mg/L (96 h)

Acute (short-term) toxicity to algae and cyanobacteria ErC50: (Desmodesmus subspicatus): 0.42 mg/L (72 h)



1260090Hard oil, whiteVersion 9.0Revision date 01-Aug-2024

Print date 01-Aug-2024

Acute (short-term) toxicity to crustacea EC50 (Daphnia magna (Big water flea)): 0.48 mg/L (48 h)

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water = 4.88 (Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4-(1-methylethylidene)-cyclohexene and 1-methyl-4-(propan-2-yl)cyclohexa-1,3-diene)

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

* The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

* No information available.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/ EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080111* - Waste paint and varnish containing organic solvents or other dangerous substances

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

Ш

Ш

SECTION 14: Transport information

14.1 UN number or ID number

UN 1263

14.2 UN proper shipping name

Land transport	(ADR/RID)
----------------	-----------

Paint

Sea transport (IMDG)

Paint

Air transport (ICAO-TI / IATA-DGR)

Paint

14

14.3 Transport hazard class(es)

	Land transport (ADR/RID)	3
	Sea transport (IMDG)	3
	Air transport (ICAO-TI / IATA-DGR)	3
.4	Packing group	
	Land transport (ADR/RID)	ш

Land transport (ADR/RID) Sea transport (IMDG) Air transport (ICAO-TI / IATA-DGR)

14.5 Environmental hazards

Land transport (ADR/RID) Sea transport (IMDG)

ENVIRONMENTALLY HAZARDOUS Marine pollutant

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

1260090 Version 9.0 Hard oil, white Revision date 01-Aug-2024

Print date 01-Aug-2024

Land transport (ADR/RID)

Tunnel restriction code: D/E Limited quantity (LQ): 5 ltr Hazard identification number (Kemler No.): 30

Sea transport (IMDG)

EmS-No.: F-E, S-E Limited quantity (LQ): 5 ltr

Air transport (ICAO-TI / IATA-DGR)

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 488 g/l

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

- VOC limit value: 2004/42/IIA(f): 700 g/l (2010)
 - Maximum VOC content of the product in a ready to use condition: 488

This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] Hazard categories / Named dangerous substances

E1 Hazardous to the aquatic environment in Category Acute 1 or Chronic 1 Quantity 1: 100t; Quantity 2: 200t P5c FLAMMABLE LIQUIDS Quantity 1: 5,000t; Quantity 2: 50,000t

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

REACH No.	Substance name	CAS No. EC No.
01-2119969963-17-xxxx	Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4- (1-methylethylidene)-cyclohexene and 1-methyl-4-(propan-2- yl)cyclohexa-1,3-diene	- 939-409-2
01-2119553060-53-0007	turpentine, oil	8006-64-2 932-349-8

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H226	Flammable liquid and vapour.		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H312	Harmful in contact with skin.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H332	Harmful if inhaled.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]			
Flam. Liq. 3	On basis of test data.		
Skin Sens. 1	Calculation method.		



1260090 Version 9.0	Hard oil, white Revision date 01-Aug-2024	Print date 01-Aug-2024
Aquatic Acute 1 Aquatic Chronic 1	Calculation method. Calculation method.	
Abbreviations and ac	cronyms	
OEL: Occupational Ex BLV: Biological limit va CAS: Chemical Abstra CLP: Classification, La CMR: Carcinogenic, M DIN: German Institute DNEL: Derived No-Eff EAKV: European Was EC: Effective Concent EC: European Commu EN: European Standal IATA-DGR: International IATA-DGR: International IACAO-TI: International IMDG Code: International IMDG Code: International ISO: International Org: LC: Lethal Concentrat LD: Lethal Dose MWC: Maximum wokp MARPOL: Maritime Po OECD: Organisation fo PBT: persistent, bioac PNEC: Predicted No E RID: Regulations conc UN: United Nations VOC: Volatile Organic vPvB: very persistent a	Alues acts Service abelling and Packaging lutagenic and Reprotoxic for Standardization / German industrial standard ect Level te Catalogue Directive ration unity rd al Air Transport Association – Dangerous Goods Regulations al Code for the Construction and Equipment of Ships carrying E Civil Aviation Organization Technical Instructions for the Safe anal Maritime Code for Dangerous Goods anization for Standardization ion lace concentration blution: The International Convention for the Prevention of Pollu or Economic Cooperation and Development cumulative, toxic Effect Concentration terning the International Carriage of Dangerous Goods by Rail Compounds and very bioaccumulative	Dangerous Chemicals in Bulk Transport of Dangerous Goods by Air
Indication of change	S	

* Data changed compared with the previous version.

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland



Discover our solutions online at ecologicalbuildingsystems.com