according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830





SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation

5170090 COLOURS FOR LIFE Satin paint, white

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Plating agent

1.3 Details of the supplier of the safety data sheet

AURO Pflanzenchemie AG

Alte Frankfurter Straße 211 Telephone: +49 531 28141-0 38122 Braunschweig Telefax: +49 531 28141-72 Deutschland E-mail: info@auro.de Website: www.auro.de

Department responsible for information

E-mail (competent person) msds@auro.de

1.4 Emergency telephone number

Emergency telephone number +44 1544388535

Only available during office hours.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

not applicable

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

not applicable

Signal word

not applicable

Hazard statements

not applicable

Precautionary statements

not applicable

Hazard components for labelling

not applicable

Supplemental hazard information

EUH208 Contains 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition / information on ingredients.

3.2 Mixtures

Description

Hazardous ingredients

Page 1/8 GB (en_GB)



according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



5170090 COLOURS FOR LIFE Satin paint, white white

Version 1.0 Revision date 18-Jan-2022 Print date 18-Jan-2022

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
2682-20-4 220-239-6 613-326-00-9	2-methylisothiazol-3(2H)-one 01-2120764690-50 Acute Tox. 3 H301 / Acute Tox. 3 H311 / Skin Corr. 1B H314 / Skin Sens. 1A H317 / Eye Dam. 1 H318 / Acute Tox. 2 H330 / Aquatic Acute 1 H400 (M = 10,00) / Aquatic Chronic 1 H410 (M = 10,00) / EUH071 Specific concentration limit (SCL): Skin Sens. 1A H317: >= 0,0015	< 0,025
3811-73-2 223-296-5 -	Pyridine-2-thiol 1-oxide, sodium salt 01-2119493385-28 Acute Tox. 4 H302 / Acute Tox. 3 H311 / Eye Irrit. 2A H319 / Acute Tox. 4 H332 / Aquatic Acute 1 H400 (M = 100,00) / Aquatic Chronic 2 H411	< 0,025

Remark

Full text of H- and EUH-statements: see section 16.Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Page 2/8 GB (en GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



5170090 COLOURS FOR LIFE Satin paint, white white

Version 1.0 Revision date 18-Jan-2022 Print date 18-Jan-2022

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. Personal protection equipment: see section 8 Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No data available

Biological limit values

No data available

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Page 3/8 GB (en GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



5170090 COLOURS FOR LIFE Satin paint, white white

Version 1.0 Revision date 18-Jan-2022 Print date 18-Jan-2022

Hand protection

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material >= 0,4 mm

Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection

Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state liquid

Colour refer to label

Safety characteristics

Odour characteristic Odour threshold not determined pН not determined Melting point/freezing point not determined Initial boiling point and boiling range not determined Flash point not determined Evaporation rate at 20°C not determined not applicable Burning time Lower explosion limit at 20°C not determined Upper explosion limit at 20°C not determined Vapour pressure at 20°C 17,109 mbar Density at 20°C 1,2 kg/l

Water solubility at 20°C partially soluble
Partition coefficient: n-octanol/water see section 12
Ignition temperature in °C not determined
Decomposition temperature not determined
Viscosity not determined
Explosive properties not relevant
Oxidising properties not relevant

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

Page 4/8 GB (en GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



5170090 COLOURS FOR LIFE Satin paint, white white

Version 1.0 Revision date 18-Jan-2022 Print date 18-Jan-2022

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Pyridine-2-thiol 1-oxide, sodium salt

LD50: oral (Rat): = 1.208 mg/kg

LC50: inhalative (Rat): = 1,08 mg/L (4 h)

LD50: dermal (Rat): = 2.000 mg/kg

LD50: oral (Rat): = 1.208 mg/kg

LC50: inhalative (Rat): = 1,08 mg/L (4 h)

LD50: dermal (Rat): = 2.000 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

Page 5/8 GB (en GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



5170090 COLOURS FOR LIFE Satin paint, white white

Version 1.0 Revision date 18-Jan-2022 Print date 18-Jan-2022

Based on available data, the classification criteria are not met.

Acute (short-term) fish toxicity 2-methylisothiazol-3(2H)-one

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 4,77 mg/L (96 h)

Pyridine-2-thiol 1-oxide, sodium salt

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 0,007 mg/L (96 h)

Method: OECD 203

Acute (short-term) toxicity to algae and cyanobacteria

2-methylisothiazol-3(2H)-one

EC50 (Selenastrum capricornutum): = 0,103 mg/L (72 h)

2-methylisothiazol-3(2H)-one

NOEC (Selenastrum capricornutum): = 0,05 mg/L (72 h)

2-methylisothiazol-3(2H)-one

EC50 (Skeletonema costatum): = 0,072 mg/L (72 h)

2-methylisothiazol-3(2H)-one

NOEC (Skeletonema costatum): = 0,072 mg/L (72 h)

Pyridine-2-thiol 1-oxide, sodium salt

NOEC (Selenastrum capricornutum): = 0,08 mg/L (72 h)

Method: OECD 201

Pyridine-2-thiol 1-oxide, sodium salt

EC50 (Selenastrum capricornutum): = 0,46 mg/L (72 h)

Method: OECD 201

Acute (short-term) toxicity to crustacea

2-methylisothiazol-3(2H)-one

EC50 (Daphnia magna (Big water flea)): = 0,934 mg/L (48 h)

2-methylisothiazol-3(2H)-one

LC50: (Mysidopsis bahia): = 2.98 mg/L (48 h)

Pyridine-2-thiol 1-oxide, sodium salt

EC50 (Daphnia magna (Big water flea)): = 0,022 mg/L (48 h)

Method: OECD 202

Chronic (long-term) toxicity to aquatic invertebrate

2-methylisothiazol-3(2H)-one

NOEC (Daphnia magna (Big water flea)): = 0,044 mg/L (21 d)

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water = -0,49

Partition coefficient: n-octanol/water = 0

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

Page 6/8 GB (en GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



5170090 COLOURS FOR LIFE Satin paint, white white

Version 1.0 Revision date 18-Jan-2022 Print date 18-Jan-2022

080120 - aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number

not applicable

14.2 UN proper shipping name

Land transport (ADR/RID)

No dangerous good in sense of these transport regulations.

Sea transport (IMDG)

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI / IATA-DGR)

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

not applicable

14.4 Packing group

not applicable

14.5 Environmental hazards

Land transport (ADR/RID) not applicable
Sea transport (IMDG) not applicable

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

not applicable

Sea transport (IMDG)

not applicable

Air transport (ICAO-TI / IATA-DGR)

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value: 0,888 q/l

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC limit value 2004/42/IIA(d): 130 g/l (2010)

Maximum VOC content (g/L) of the product in a ready to use condition: 0.8881

This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

Page 7/8 GB (en GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



5170090 COLOURS FOR LIFE Satin paint, white white

Version 1.0 Revision date 18-Jan-2022 Print date 18-Jan-2022

This product is not classified according to Directive 2012/18/EU.

National regulations

15.2 Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

REACH No.	Substance name	CAS No.	EC No.
01-2120764690-50	2-methylisothiazol-3(2H)-one	2682-20-4	220-239-6
01-2119493385-28	Pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5

SECTION 16: Other information

Relevant R-, H- and EUH-phrases (Number and full text)Relevant R-and H-phrases (Number and full text):

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

not applicable

H411

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

Toxic to aquatic life with long lasting effects.

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration EC: European Community EN: European Standard

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

MWC: Maximum wokplace concentration

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

Indication of changes

Page 8/8 GB (en GB)

^{*} Data changed compared with the previous version

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland

