



Technical data

Material	
Main component	PET

Property	Regulation	Value
Colour		White
Surface weight		63 g/m ²
Thickness		0.7 mm
Tensile strength MD/CD		90 N/5 cm / 145 N/5 cm
Elongation MD/CD		75 % / 90 %
Installation temperature		5 °C to 60 °C ; 40 °F to 140 °F

Areas of application

AEROSANA FLEECE is a supplementary product for working with spray-on or brush-on seals from the AEROSANA VISCONN family. It can be used to reliably cover cracks or joints that are wider than 3 mm in the case of AEROSANA VISCONN or 20 mm in the case of AEROSANA VISCONN FIBRE.

Supply forms

Art. no.	GTIN	Length	Width	Weight	Sales unit	Container
1AR01715	4026639217158	25 m	150 mm	0.624 kg	1	90

Advantages

- ✓ Reliable airtightness and windtightness: Tested as part of the AEROSANA VISCONN system
- ✓ Easy to work with: Very malleable fleece material
- ✓ Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme

Substrates

AEROSANA FLEECE can be used on subsurfaces that are slightly uneven and/or structured. To achieve airtight and/or windtight installation, it is important that AEROSANA FLEECE is coated with AEROSANA VISCONN or AEROSANA VISCONN FIBRE on both sides in the area where it is in contact with the subsurface. Recommendations for subsurfaces that AEROSANA VISCONN products can be used on can be found in the relevant application recommendations.

Tested for hazardous substances according to



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:

Phone: +353 46 9432104

Fax: +353 46 9432435

info@ecologicalbuildingsystems.com

For Stockists contact

Ireland

Phone: +353 (0)46 9432104

Fax: +353 (0)46 9432435

UK

Phone: +44 (0)1228 711 511

Fax: +44 (0)1228 712 280

Ecological Building Systems

info@ecologicalbuildingsystems.com

www.ecologicalbuildingsystems.com

MOLL bauökologische Produkte GmbH

Rheintalstraße 35 - 43

68723 Schwetzingen

Germany

www.proclima.com

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511

Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd.,
Cardewlees, Carlisle, Cumbria, CA5 6LF,
United Kingdom

Ireland Ecological Building Systems Ltd.,
Main Street, Athboy. Co. Meath, C15 Y678,
Republic of Ireland