

	0000 sion 6.0	COLOURS FOR LIFE Paint primer Revision date 01-Aug-2024	Print date 01-Aug-202		
SE	CTION 1: Identification of th	ne substance/mixture and of the company/underta	aking		
1.1	Product identifier				
	Trade name/designation				
	5100000	COLOURS FOR LIFE Paint primer			
1.2	Relevant identified uses of the	e substance or mixture and uses advised against			
	Relevant identified uses				
	Plating agent				
1.3	Details of the supplier of the s	safety data sheet			
	Supplier				
	AURO Pflanzenchemie AG				
	Alte Frankfurter Straße 211 A	Telephone: +49 531 28141-0			
	38122 Braunschweig	Telefax: +49 531 28141-72 E-mail: info@auro.de			
	Germany	Website: www.auro.de			
	Department responsible for in	formation			
	E-mail (competent person)	msds@auro.de			
.4	Emergency telephone number	r			
	Emergency telephone number:				
	Only available during office hou				
SE	CTION 2: Hazards identifica	ition			
2.1	Classification of the substance	e or mixture			
	Classification according to Re	egulation (EC) No 1272/2008 [CLP]			
	The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].				
2.2	Label elements	Label elements			
	Labelling according to Regulation (EC) No. 1272/2008 [CLP]				
	Hazard pictograms				
	not applicable				
	Signal word				
	not applicable				
	Hazard statements				
	not applicable				
	Precautionary statements				
	not applicable				
	Hazard components for labelling				
	not applicable				
	Supplemental hazard informa				
		rning! Hazardous respirable droplets may be formed when s	sprayed. Do not breathe spray or mist.		
2.3	Other hazards				
		lo not meet the PBT/vPvB criteria according to REACH, ann	iex XIII.		
SE	CTION 3: Composition/info	rmation on ingredients.			
3.2	Mixtures				
	Description				
	Hazardous ingredients				
	CAS No.	Substance name	woight %		



 5100000
 COLOURS FOR LIFE Paint primer

 Version 6.0
 Revision date 01-Aug-2024
 Print date 01-Aug-2024

 / Acute Tox. 3 H331 / STOT RE 1 H372 / Aquatic Acute 1 H400 (M = 100,00) / Aquatic Chronic 2
 // Att / EUH070

 ATE (oral): = 500 mg/kg bw
 ATE (inhalative): = 0.5 mg/m³ (4 h)

 ATE (dermal): = 790 mg/kg bw
 ATE (dermal): = 790 mg/kg bw

Remark

Full text of H- and EUH-statements: see section 16.Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up



5100000	COLOURS FOR LIFE Paint primer
Version 6.0	Revision date 01-Aug-2024

Print date 01-Aug-2024

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: refer to section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. Personal protection equipment: see section 8 Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Storage class LGK12 - non-combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No data available Biological limit values No data available

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber) Thickness of the glove material >= 0.4 mm Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles:EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166

Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Environmental exposure controls

AURO

5100000 Version 6.0 COLOURS FOR LIFE Paint primer Revision date 01-Aug-2024

Print date 01-Aug-2024

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	refer to label
Odour	characteristic
рН	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	not determined
flammability	not applicable
Lower explosion limit at 20°C	not determined
Upper explosion limit at 20°C	not determined
Vapour pressure at 20°C	33.333 mbar
Relative vapour density	not applicable
Density at 20 °C	1.2 kg/l
Water solubility at 20°C	practically insoluble
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	not determined
Decomposition temperature	not determined
Viscosity at 40 °C:	not determined

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

- Pyridine-2-thiol 1-oxide, sodium salt
- LD50: oral (Rat): = 500 mg/kg bw
- * LC50: inhalative (Rat): = 0.5 mg/m³ (4 h)
- * LD50: dermal (Rat): = 790 mg/kg bw

Print date 01-Aug-2024

5100000		
Version 6.0		

COLOURS FOR LIFE Paint primer Revision date 01-Aug-2024

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Based on available data, the classification criteria are not met.

- Acute (short-term) fish toxicity
 Pyridine-2-thiol 1-oxide, sodium salt
 LC50: (Danio rerio (zebrafish)): = 0.008 mg/L (96 h)
 Method: OECD 203
- Acute (short-term) toxicity to algae and cyanobacteria
 - NOEC (Selenastrum capricornutum): = 0.08 mg/L (72 h) Method: OECD 201

ErC50: (Selenastrum capricornutum): = 0.46 mg/L (72 h) Method: OECD 201

Acute (short-term) toxicity to crustacea

EC50 (Daphnia magna (Big water flea)): = 0.022 mg/L (48 h) Method: OECD 202

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water = -1.09 (Pyridine-2-thiol 1-oxide, sodium salt)

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties No information available.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations



	000 on 6.0	COLOURS FOR LIFE Paint primer Revision date 01-Aug-2024	Print date 01-Aug-2024	
42.4	Weste treatment method	•	<u> </u>	
-	Waste treatment method			
	Product/Packaging dispo			
	EC, covering waste and da	•	aste disposal according to directive 2008/98/	
		gnations according to EWC/AVV		
		sions containing paint or varnish other than those mention	ed in 08 01 19	
	Other disposal recomme			
	Non-contaminated packag	es may be recycled. Vessels not properly emptied are spe	cial waste.	
SEC	TION 14: Transport in	formation		
14.1	UN number or ID number	r		
	not applicable			
14.2	UN proper shipping nam	e		
	Land transport (ADR/RID)			
	No dangerous good in sense of these transport regulations.			
	Sea transport (IMDG)			
	No dangerous good in sense of these transport regulations.			
	Air transport (ICAO-TI / IATA-DGR)			
	No dangerous good in sense of these transport regulations.			
14.3	Transport hazard class(e	es)		
not applicable				
14.4	Packing group			
	not applicable			
14.5	Environmental hazards			
	Land transport (ADR/RID)	not applicable		
	Sea transport (IMDG)	not applicable		
	Special precautions for u			
	Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8			
14.7	Maritime transport in bul	k according to IMO instruments		
	No transport as bulk accor	ding to IBC Code.		
14.8	Additional information			
	Land transport (ADR/RID			
	not applicable			
	Sea transport (IMDG)			
	not applicable			
	Air transport (ICAO-TI / I/			

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 1 g/l

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC limit value: 2004/42/IIA(d): 130 g/l (2010)

Maximum VOC content of the product in a ready to use condition: 1

This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.



5100000	COLOURS FOR LIFE Paint primer	
Version 6.0	Revision date 01-Aug-2024	Print date 01-Aug-2024

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] Hazard categories / Named dangerous substances

This product is not classified according to Directive 2012/18/EU.

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

REACH No.	Substance name	CAS No. EC No.
01-2119493385-28	,	3811-73-2 223-296-5

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

	······································
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H372	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
EUH070	Toxic by eye contact.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP] not applicable

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration

EC: European Community

EN: European Standard

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

MWC: Maximum wokplace concentration

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic

PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.

For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



Email us

info@ecologicalbuildingsystems.com



Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland



Discover our solutions online at ecologicalbuildingsystems.com