

MOLL

Declaration of Performance

DoP-No.: 4026639158222-033802

① **CONSTIVAP 2.3 PLUS**

② 15822

(batch number see imprint on membrane)

Humidity-variable vapour check and airtightness membrane, suitable for all fibrous insulation materials

④ MOLL bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany

System 3

The notified body "Gesellschaft für Materialforschung und Prüfungsanstalt für Bauwesen mbH" - NB 0800 - carried out the initial tests of the material properties according to system 3.

⑨ **Performance declared according to BS EN 13984 - Typ B**

Attribute	Norm	Value
Length ¹	BS EN 1848-2:2001	50 m
Width ²	BS EN 1848-2:2001	1.5 m
Surface weight	BS EN 1849-2:2001	90 ±5 g/m ²
Thickness	BS EN 1849-2:2001	0.2 ±0.05 mm
sd-value	BS EN 1931:2001	2.30 ±0.25 m
g-value		11.5 ±1.25 MN·s/g
Reaction to fire		E
Tensile strength MD/CD	BS EN 13859-1:2010, Anhang A	355 N/5 cm / 285 N/5 cm
Elongation MD/CD	BS EN 12311-2:1999	15 % / 15 %
Nail tear resistance MD/CD	BS EN 13859-1:2010, Anhang B	240 N / 200 N
Artificial ageing by long term	BS EN 1296:2001 / BS EN 1931:2001	passed

dimensional tolerances: ¹: +0.5 m; ²: +0.005 m

The performance of the product according to numbers 1 and 2 correspond to the performance declared according to number 9. According to number 4, the manufacturer is solely responsible for issuing this Declaration of Performance. Signed for the manufacturer and on behalf of the manufacturer by:



Lothar Moll, Geschäftsführer



Michael Förster, Leiter Technik

Schwetzingen, 05/03/2019