BUILDING | CONSTRUCTION CELENIT range

 $\square$ 





Thermal and acoustic insulation board, consisting of mineralized fir wood wool bound with grey Portland cement. Wood wool is 3 mm wide.

It complies with EN 13168 and EN 13964 standards. The boards are certified by ANAB-ICEA and natureplus for eco-compatibility of materials and manufacturing process. CELENIT N is PEFC<sup>™</sup> certified. Also available with FSC<sup>®</sup> certification. **Edges detail** D - BC - BL - B4

#### Applications

roofs, external walls, partitions, ceilings, thermal bridges, insulated concrete

## **Technical data**

Standard	EN 13168 - EN 13964									
Designation code	WW-EN13168-L2-W1-T1-S2-CS(10)200-Cl1 (thicknesses 15-40 mm) CE WW-EN13168-L2-W1-T1-S2-CS(10)150-Cl1 (thicknesses 50-75 mm)									
Length x Width [mm]	2400x600 - 2000x600 - 1200x600									
Thickness [mm]	15	20	25	30	35	40	50	75		
Weight [kg/m²]	8.0	10.0	11.5	13.0	14.0	16.5	19.0	26.0		
Declared thermal conductivity $\lambda_{D}$ [W/mK]	0.065									
Declared thermal resistance $R_D$ [m <sup>2</sup> K/W]	0.20	0.30	0.35	0.45	0.50	0.60	0.75	1.15		
Thermal resistance R [m²K/W]	0.23	0.31	0.38	0.46	0.54	0.61	0.77	1.15		
Compressive stress at 10% deformation $\sigma_{10}$ [kPa]	≥ 200 (thicknesses 15-40 mm) ≥ 150 (thicknesses 50-75 mm)									
Water vapour transmission µ	5									
Specific heat c <sub>P</sub> [kJ/kgK]	1.81 Certified by the University of Bologna - LEBSC no. 809   rev. 07.05.2009									
Reaction to fire	Euroclass B-s1, d0									
Chloride content [%]	≤ 0.35									
Durability	Class C									
Release of formaldehyde	Class E1									
Release of asbestos	it does not contain asbestos									

### Logistic data

Dimensioni [mm]	Pallet	15 mm	20 mm	25 mm	30 mm	35 mm	40 mm	50 mm	75 mm
boards: 2400x600	boards per pallet	130		88		64		44	
pallet: 2400x1200	m² per pallet	187.20		126.72		92.16		63.36	
boards: 2000x600	boards per pallet	130	110	88	74	64	56	44	30
pallet: 2000x1200	m² per pallet	156.00	132.00	105.60	88.80	76.80	67.20	52.80	36.00
boards: 1200x600	boards per pallet	130		88					
pallet: 1200x1200	m² per pallet	93.60		63.36					

# Certifications

ISO 9001:2015 no. 1351 ANAB no. EDIL 2009\_004 NATUREPLUS no. 1007-1511-134-1 EPD® S-P-02275 FSC® no. ICILA-COC-002789 PEFC™ no. ICILA-PEFCCOC-000117 ICEA no. LEED 2015\_001 ICEA no. REC 2015\_001





2023/07 | page 1/2

BUILDING | CONSTRUCTION CELENIT range



# Storage

The boards must be transported and laid on a flat surface in a clean and dry place, protected from direct moisture.

Pallet handling on site will be performed with the necessary care. Bumps at the corners of the pallets can cause damage to the boards.

Store the boards indoor; boards must be not in direct contact to the ground and protected from moisture and atmospheric agents. During the storage of pallets on site, make sure to not remove the plastic wrapping. The boards must be dry at the time of installation as the place on which they are going to be installed.



The boards have one side that should be placed against the structure (back of the board). The back of the board usually has CELENIT logo. In the absence of the logo it is possible to identify the front according to the

pallet's layout: the front of the boards is towards the top and the back down towards the pallet.

If the boards were for indoor use, before installation they must remain in the room to adapt to the temperature and humidity, for a few days. Avoid sudden temperature increases, just after the application of the boards.

The data of the present technical data sheet is correct at the time of release. CELENIT S.p.A. is continuously improving the products, therefore this technical data sheet can be up-dated without prior notice. Please contact our technical assistance to get the latest release.

CELENIT S.p.A Thermal and acoustic insulation panels for a sustainable architecture Registered office: Via Bellinghiera, 17 35019 Onara di Tombolo (PD) Italy P.IVA/C.F.: 00211210281 2023/07 | page 2/2

Contact: Ph. +39.049.5993544 techsupport@celenit.com www.celenit.com For over 20 years, Ecological Building Systems has been at the forefront of environmental and sustainable building products supplying a range of innovative airtightness solutions and natural insulations backed up with expert technical support.

As product suppliers in the UK and Ireland, we're happy to assist you with your projects and have expert technical and sales advice on hand.



#### Call us

Great Britain +44 (0)1228 711511 Ireland +353 46 9432104



#### Email us

info@ecologicalbuildingsystems.com



#### Find us

Great Britain Ecological Building Systems UK Ltd., Cardewlees, Carlisle, Cumbria, CA5 6LF, United Kingdom

Ireland Ecological Building Systems Ltd., Main Street, Athboy. Co. Meath, C15 Y678, Republic of Ireland



Discover our solutions online at ecologicalbuildingsystems.com